WP Series

WEATHERPROOF MULTI TONE AUDIO VISUAL ALARM



Mechanical Data

Material : FRP

Weight :3 Kg (approx.)

IP Protection : IP 65 as per IS 13947 / 1993 / IEC 60529 / 1989

Finish : Grey. Cable Entry : 2 x 3/4" ET Gasket : Neoprene : Stainless Steel Hardware

Electrical Data


: 24 V DC or 110 V / 230 V AC - 50 Hz Voltage

Out put Current :800 mA Power rating : 18 Watt Sound Output :112 db Terminals : 4 x 4 sq mm Earthing: External : 2 Nos. - M6 : Internal : 1 No. - M5

Description



Weather proof Multi-tone Audio Visual Alarm with integral terminal chamber. The sounder unit and lamp unit either LED cluster or Xenon lamp are interconnected. The unit is duly wired up to the terminals for wiring through WP cable glands. The covers are provided with neoprene '0' ring for weatherproof protection.(IP - 65) Suitable for interfacing with Fire Alarm / Gas detection Systems / Telephone ring sounder.



Type of protection Weatherproof Area Classification **TP 65**

Apparatus Standard IS - 13947/1993/IEC 60529 / 1989

Salient Features

This unit incorporates a Telephone line interfaced audio visual alarm with the following facilities.

- Xenon Flashing system
- Melodious high volume ring tone outputs. Optionally can be used as a Hooter.
- Stainless steel mounting accessories.
- DPST Switch can be provided optionally to switch OFF / ON the Hooter along with fuse.

